## WELL BUYING INDUSTRIAL CO., LTD 🚺

Feature :

TACT SWITCH

BUTTON

NAVIGATION

MEMBRANE SWITCH

led light Bar

SLIDE

ROTARY

ROCKER SWITCH

DETECT

ENCODER

INTERRUPTER

MINIATURE MICRO SWITCH

TELEPHONE HOOK SWITCH

DOOR SWITCH

MINI SIZE

KNOB

CAP SYMBOL Bi-color LED illuminated available 2P2T, 4P2T Lock / non-lock function

## Application :


Computer products Instrumentation



| SWITCH SPECIFICATIONS       |   |  |  |  |  |
|-----------------------------|---|--|--|--|--|
| POLE - POSITION             | 2P2T,4P2T<br>LOCK / NON-LOCK Action with LED              |  |  |  |  |
| CONTACT RATING              | 30 V DC , 0.3 A   |  |  |  |  |
| CONTACT RESISTANCE          | 20 mΩ MAX. 1.5 V DC ; 100 mA<br>by Method of Voltage DROP |  |  |  |  |
| INSULATION RESISTANCE       | 100 MΩ MIN. 500 V DC                                      |  |  |  |  |
| DIELECTRIC STRENGTH         | Breakdown is not Allowable ;<br>500 V AC for 1 Minute     |  |  |  |  |
| OPERATING FORCE             | 200 ± 100 gf  |  |  |  |  |
| OPERATING LIFE              | 10,000 cycles   |  |  |  |  |
| OPERATING TEMPERATURE RANGE | -20°C ~ 70°C  |  |  |  |  |
| TOTAL TRAVEL                | TRAVEL : 2.5 ± 0.3 mm<br>TRAVEL : 3.3 ± 0.3 mm            |  |  |  |  |

| LED SPECIFICATIONS                                       |      |                   |               |      |        |        |       |       |  |
|--|------|-------------------|---------------|------|--------|--------|-------|-------|--|
| ATTENTION<br>LEDs are Electrostatic<br>Sensitive devices | Unit | Value / LED Color |               |      |        |        |       |       |  |
|  |      | Blue              | Pure<br>Green | Red  | Yellow | Orange | Green | White |  |
| LUMINOUS INTENSITY@20mA<br>Iv                            | mcd  | 900               | 6500          | 900  | 1300   | 900    | 400   | 1200  |  |
| Dominant Wavelength<br>λD                                | nm   | 470               | 525           | 635  | 590    | 601    | 570   | 7     |  |
| FORWARD VOLTAGE@20mA<br>Vf                               | v    | 3.2               | 3.3           | 1.95 | 2      | 2.1    | 2.1   | 4     |  |

A single bin cannot be ordered, please contact us in advance if you need a particular bin sorting before placing your order to clarify the lead time, MOQ and pricing





WB

## ML SERIES

